

Auswahltabelle für Hydraulikschläuche

Nenn- durch- messer	6	8	10	12	16	20	25	32	40	50	Nenn- durch- messer	
	Zoll	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"		Zoll
	Size	-4	-5	-6	-8	-10	-12	-16	-20	-24		-32
Schlauch- TYP	Maximaler Arbeitsdruck in bar										NORM BEZ.	
101	25	20	20	16	16	12	12				1 TE	
102	75	68	63	58	50	45	40	35			2 TE	
103	145	130	110	93	80	70	55	45	40	33	3 TE	
150	225	215	180	160	130	105	88	63	50	40	1 SN	
153	225	215	180	160							Werknorm	
170	300	295	275	240	190	155	140				Werknorm	
250	400	350	330	275	250	215	165	125	90	80	2 SN	
255	400	350	330	275	250	215	165				2 SC	
450	450		445	415	350	350					4 SP	
460					450	420	380	325	290	250	4 SH	
470						420	420	420	420		R 15	
650								345	345	345	R 13 ⁶ SP	
707	190	170	155	135							R 7	
709	345	310	275	240							R 8	
704						21	17	14	10	7	R 4	
808	255	210	175	145	115	85	60				TEF	

Den aktuellen Mindestberstdruck entnehmen Sie bitte der jeweiligen Schlauchtabelle!

TEMME

Oberschwarza 62, A-8471 Spielfeld, Tel.: +43-(0)3453-20546 Fax: +43-(0)3453-20546-4

www.nfz-temmel.at